

**Item description : I348**
**Vacuum bench B3 spraying system S4 and tank CO assembled and installed**

The machine is composed by:-Vacuum bench created to be placed on the working plane and equipped with a silent and powerful engine to contain even more the nebulized adhesive. -Spray gun G6 with ergonomic handle which makes it an efficacious and precise alternative to the brush. The spray gun can perform a jet of glue from a minimum of 3 mm up to a maximum of 50 mm. -Stainless steel tank 10 lt. capacity treated with non-stick Teflon.

The vacuum module can be used in different ways: putting it on an existing table and making an hole on the plane, simply by putting it on a working table in order to have the intake on the plane or by placing it vertically to have the intake in front of you. These characteristics make it suitable to all working realities. The spray gun has been created to extend the advantages of using water based adhesives also during the assembling phases where solvent based adhesive are still widely used.



The operator, after starting the machine, can place the materials on the working plane so to make maximum use of the intake on the working plane for both keeping the materials standing and absorbing the nebulized adhesive. All the spray gun functions can be adjusted: quantity of adhesive, width of jet and quality of distribution even on different thicknesses. For a proper functioning of the vacuum bench it is recommended to replace the filter each time is visibly dirty or when the vacuum bench is not intaking properly. A jet of air immediately before and after the adhesive nebulization keeps the nozzle constantly clean. Our systems are maintenance free. The tank is conceived in a way that allow the use of the adhesive in bag in box avoiding to make dirty the tank and to filter the glue thus preventing the contact with air which can alter its properties.

**Specific:**

Capacity m <sup>3</sup> / h : 800	Volt : 230	Prevalence : 70	Hertz : 50
Watt : 36	Bar exercise : 6	Decibel (dB) : 63.3	Ampere : 0.31/0.36
Air lt / min : 30	Effective width cm : 60	Usable depth cm : 37	Average consumption :
Gross Weight kg : 30.430	Tare Kg : .000	Length mt : 0.67	Height mt : 0.64
Net Weight kg : 30.430	Net Weight kg : ...	mt Width : 0.55	Volume m <sup>3</sup> : 0.235

**Intercom Srl** ® - P.iva e C.F. 06183210480

**Address:** Via della Gora, 13 - 50025 Montespertoli - Firenze - Italia

**Phone:** +39 0571 671096 - **Fax:** +39 0571 671151 - **Email:** info@intercomsas.it - **Web:** www.intercomsas.it